
SLC Series SUBMINATURE HIGH POWER RELAY 16A/20A/30A

E179944

R50056114

CQC08002027666
CQC08002027668



RoHS Compliant

Features

- Miniature volume, PCB usage
- Contact rating: 16A/20A/30A
- Temperature range: +85℃/+105℃

Ordering Information

SLC-12VDC-S L-C

- A / B / C — Contact arrangment
- L0.9W — Coil Power
- S sealed / F dustproof — Construction
- 5V / 6V / 9V / 12V 18V / 24V/36V/48V — Coil Voltage
- Part number

Contact Rating

Contact a rrangment	A / B / C
Contact resistance	100mΩ
Contact material	Silver alloy: AgCdO、AgSnO2、AgNi
Contact rating	1HP/16A/120VAC 20A/250VAC 30A/250VAC
Max switching voltage	250VAC
Max switching current	30A
Max switching power	7200VA
Electrical endurance (frequency: 1800 ops/h)	$1x10^5$ Ops / $1x10^4$ Ops
Mechanical endurance (frequency: 18000 ops/h)	$1x10^7$ Ops

Characteristics

Insulation system		B / F
Insulation resistance		100MΩ (500VDC)
Dielectric Strength Leakage current 1mA	Between contacts and coil	2000VAC 1 minute
	Between open contacts	1500VAC 1 minute
Operate time(Under nominal voltage)		≤10ms
Release time(Under nominal voltage)		≤10ms
Humidity		45% ~85% RH（20℃）
Ambient Temperature		-40℃~+85℃/-40℃~+105℃
Shock resistance	Functional	98m/s²
	Destructive	980m/s²
Vibration resistance （Double amplitude）		10Hz~55Hz 1.5mm
Weight		Approx 34g
Construction		Sealed

Remark:1)All above data is initial value

Coil Data （at 20℃）

Power dissipation W	Voltage VDC	Current mA	Resistance Ω±10%	Pick-up voltage	Drop-out voltage	Max allowable
0.9W (L)	05	185	27	75%Max	10%Min	130%
	06	150	40			
	09	100	90			
	12	75	160			
	18	50	380			
	24	37.5	640			
	36	25	1440			
	48	18.75	2560			

This product specification only for your reference, we will not notify you if we do any improvement. We reserve all the right for the final explanation

松乐继电器 SONGLE RELAY

Web：www.songle.com www.songlerelay.com

Add.：CW7, Zone A, Far East Industrial Park, Yuyao City, Zhejiang, China Zip Code：315400

www.songle.com www.songlerelay.com

SLC Series SUBMINATURE HIGH POWER RELAY 16A/20A/30A


Safety Approval Ratings

CQC CQC08002027666 CQC08002027668	R50056114	cULus E179944
30A 250VAC 20A 250VAC	30A 250VAC 20A 250VAC	20A 240VAC 1HP 16A 120VAC


OUTLINE DIMENSIONS ,WIRING DIAGRAM AND PC BOARD LAYOUT

Unit:mm

Physical installation diagram




Bottom view diagram




Bottom view diagram B Tolerance：±0. 1mm


PCB board diagram
（bottom view diagram）



Conversion C type



Normally open A type



Normally closed B type

This product specification only for your reference, we will not notify you if we do any improvement. We reserve all the right for the final explanation

松乐继电器 SONGLE RELAY
Web：www.songle.com www.songlerelay.com
Add.：CW7, Zone A, Far East Industrial Park, Yuyao City, Zhejiang, China Zip Code：315400